


呼び径		各部の寸法					二面幅 S		材質
A (mm)	B (inch)	R	Rc	L	E	f	八角	十角	
25×15	1×1/2	R 1	Rc 1/2	27	20	13	35		①
25×20	1×3/4	R 1	Rc 3/4	27	20	15	35		①
32×15	1 1/4 × 1/2	R 1 1/4	Rc 1/2	32.5	23.5	12	43		②
32×20	1 1/4 × 3/4	R 1 1/4	Rc 3/4	32.5	23.5	13	43		②
32×25	1 1/4 × 1	R 1 1/4	Rc 1	32.5	23.5	15	43		②
40×15	1 1/2 × 1/2	R 1 1/2	Rc 1/2	33.5	23.5	15	49		②
40×20	1 1/2 × 3/4	R 1 1/2	Rc 3/4	33.5	23.5	13	49		②
40×25	1 1/2 × 1	R 1 1/2	Rc 1	33.5	23.5	15	49		②
40×32	1 1/2 × 1 1/4	R 1 1/2	Rc 1 1/4	33.5	23.5	21	49		②
50×20	2 × 3/4	R 2	Rc 3/4	37.5	26.5	13	61		②
50×25	2 × 1	R 2	Rc 1	37.5	26.5	15	61		②
50×32	2 × 1 1/4	R 2	Rc 1 1/4	37.5	26.5	17	61		②
50×40	2 × 1 1/2	R 2	Rc 1 1/2	37.5	26.5	17	61		②
65×40	2 1/2 × 1 1/2	R 2 1/2	Rc 1 1/2	39	28	18		80	②
65×50	2 1/2 × 2	R 2 1/2	Rc 2	39	28	20		80	②
80×40	3 × 1 1/2	R 3	Rc 1 1/2	44	32	18		95	②
80×50	3 × 2	R 3	Rc 2	44	32	20		95	②
80×65	3 × 2 1/2	R 3	Rc 2 1/2	44	32	23		95	②

(注記) 管用ねじ部はJIS B 0203:1999による。

*材質①SUS F304, ②SCS 13A。

承認 芦田	材質 SUS F304 SCS 13A	製品名 ブッシング	図面番号 16280
検図 今西	尺度 フリー	製品コード B	
製図 滝川	日付 2016.10.14	 イノック株式会社	