



呼び径①×②		OD1	OD2	S20S				H	許容差					
A	B			ID1	T1	ID2	T2		OD1	OD2	ID1	ID2	T1・T2	H
20×15	3/4×1/2	27.2	21.7	22.2	2.5	16.7	2.5	38.1	+1.6 -0.8		±0.8			
25×20	1×3/4	34.0	27.2	28.0	3.0	22.2	2.5	50.8						
25×15	1×1/2	34.0	21.7	28.0	3.0	16.7	2.5	50.8						
32×25	1 1/4×1	42.7	34.0	36.7	3.0	28.0	3.0	50.8						
32×20	1 1/4×3/4	42.7	27.2	36.7	3.0	22.2	2.5	50.8						
40×32	1 1/2×1 1/4	48.6	42.7	42.6	3.0	36.7	3.0	63.5						
40×25	1 1/2×1	48.6	34.0	42.6	3.0	28.0	3.0	63.5						
40×20	1 1/2×3/4	48.6	27.2	42.6	3.0	22.2	2.5	63.5						
40×15	1 1/2×1/2	48.6	21.7	42.6	3.0	16.7	2.5	63.5						
50×40	2×1 1/2	60.5	48.6	53.5	3.5	42.6	3.0	76.2						
50×32	2×1 1/4	60.5	42.7	53.5	3.5	36.7	3.0	76.2						
50×25	2×1	60.5	34.0	53.5	3.5	28.0	3.0	76.2						
50×20	2×3/4	60.5	27.2	53.5	3.5	22.2	2.5	76.2						
50×15	2×1/2	60.5	21.7	53.5	3.5	16.7	2.5	76.2						
65×50	2 1/2×2	76.3	60.5	69.3	3.5	53.5	3.5	88.9						
65×40	2 1/2×1 1/2	76.3	48.6	69.3	3.5	42.6	3.0	88.9						
65×32	2 1/2×1 1/4	76.3	42.7	69.3	3.5	36.7	3.0	88.9						
65×25	2 1/2×1	76.3	34.0	69.3	3.5	28.0	3.0	88.9						
80×65	3×2 1/2	89.1	76.3	81.1	4.0	69.3	3.5	88.9						
80×50	3×2	89.1	60.5	81.1	4.0	53.5	3.5	88.9						
80×40	3×1 1/2	89.1	48.6	81.1	4.0	42.6	3.0	88.9						
80×32	3×1 1/4	89.1	42.7	81.1	4.0	36.7	3.0	88.9						
80×25	3×1	89.1	34.0	81.1	4.0	28.0	3.0	88.9						

※ ベベルエンドの形状、寸法はJIS B 2313「配管用銅板製突合せ溶接式管継手」による

※ 管継手の直角度の許容値はJIS B 2313「配管用銅板製突合せ溶接式管継手」による

承認 滝川	材質 SUS 304W	名称 同心レジューサー RC(S20S)	図面番号
検図 芦田	尺度 フリー		17225
製図 滝川	日付 2017/7/21	<b>inoc</b> イノック株式会社	