



呼び径①×②×③		OD1	OD2	S10S				C	M	許容差					
A	B			ID1	T1	ID2	T2			OD1	OD2	ID1	ID2	T1・2	C・M
100x100x80	4x4x3	114.3	89.1	108.3	3.0	83.1	3.0	104.8	98.4	±1.6	+1.6 -0.8	±1.6	±1.6	+規定 しない -12.5%	±1.6
100x100x65	4x4x2½	114.3	76.3	108.3	3.0	70.3	3.0	104.8	95.3						
100x100x50	4x4x2	114.3	60.5	108.3	3.0	54.9	2.8	104.8	88.9						
100x100x40	4x4x1½	114.3	48.6	108.3	3.0	43.0	2.8	104.8	85.7						
125x125x100	5x5x4	139.8	114.3	133.0	3.4	108.3	3.0	123.8	117.5	+2.4 -1.6	±1.6	±1.6	+規定 しない -12.5%	±1.6	
125x125x80	5x5x3	139.8	89.1	133.0	3.4	83.1	3.0	123.8	111.1						
125x125x65	5x5x2½	139.8	76.3	133.0	3.4	70.3	3.0	123.8	108.0						
150x150x125	6x6x5	165.2	139.8	158.4	3.4	133.0	3.4	142.9	136.5						
150x150x100	6x6x4	165.2	114.3	158.4	3.4	108.3	3.0	142.9	130.2						
150x150x80	6x6x3	165.2	89.1	158.4	3.4	83.1	3.0	142.9	123.8						
150x150x50	6x6x2	165.2	60.5	158.4	3.4	54.9	2.8	142.9	115.9	+4.0 -3.2	+2.4 -1.6	±1.6	±1.6	±2.4	
200x200x150	8x8x6	216.3	165.2	208.3	4.0	158.4	3.4	177.8	168.3						
200x200x125	8x8x5	216.3	139.8	208.3	4.0	133.0	3.4	177.8	161.9						
200x200x100	8x8x4	216.3	114.3	208.3	4.0	108.3	3.0	177.8	155.6						
250x250x200	10x10x8	267.4	216.3	259.4	4.0	208.3	4.0	215.9	203.2	+4.0 -3.2	+2.4 -1.6	±3.2	±3.2	±2.4	
250x250x150	10x10x6	267.4	165.2	259.4	4.0	158.4	3.4	215.9	193.7						
300x300x250	12x12x10	318.5	267.4	309.5	4.5	259.4	4.0	254.0	241.3						
300x300x200	12x12x8	318.5	216.3	309.5	4.5	208.3	4.0	254.0	228.6						
300x300x150	12x12x6	318.5	165.2	309.5	4.5	158.4	3.4	254.0	219.1						

※ ベベルエンドの形状、寸法はJIS B 2313「配管用鋼板製突合せ溶接式管継手」による

※ 管継手の直角度の許容値はJIS B 2313「配管用鋼板製突合せ溶接式管継手」による

承認 滝川	材質 SUS 304W	名称 径違いチーズ	図面番号
検図 芦田	尺度 フリー	TR(S10S)	17236
製図 滝川	日付 2017/7/21	inoć イノック株式会社	