



呼び径 (A)	フランジ各部の寸法							寸法許容差					
	差込み 穴の径 d	外径 D	厚さ t	中心円 の径 C	ボルト穴 数 径		隣接穴 のピッチ P	d	D	t	C	P	
					n	h							
150	166.6	280	22	240	8	23	91.84	+1 0	±1.5	+2 0	±0.8	±0.8	
200	218.0	330	22	290	12	23	75.06						
250	269.5	400	24	355	12	25	91.88						
300	321.0	445	24	400	16	25	78.04						
350	358.1	490	26	445	16	25	86.82						
400	409.0	560	28	510	16	27	99.50	+1.5 0	±3	+2 0	±0.8	±0.8	
450	460.0	620	30	565	20	27	88.39						
500	511.0	675	30	620	20	27	96.99						
550	562.0	745	32	680	20	33	106.38	+2 0	±3	+2 0	±0.8	±0.8	
600	613.0	795	32	730	24	33	95.28						
650	664.0	845	34	780	24	33	101.81						
700	715.0	905	34	840	24	33	109.64						
750	766.0	970	36	900	24	33	117.47						

承認	滝川	材質	SUSF304	名称	呼び圧力10Kフランジ 差込み溶接フランジ FF	図面番号	19503
検図	今西	尺度	フリー				
製図	芦田	日付	2019/11/15	 イノック株式会社			