



呼び径 (A)	フランジ各部の寸法							寸法許容差				
	差込み 穴の径	外径	厚さ	中心円 の径	ボルト穴 数	径	隣接穴 のピッチ	d	D	t	C	P
	d	D	t	C	n	h	P					
10	17.8	90	14	65	4	15	45.96	+1.0 0	±1.5	+1.5 0	±0.8	±0.8
15	22.2	95	14	70	4	15	49.50					
20	27.7	100	16	75	4	15	53.03					
25	34.5	125	16	90	4	19	63.64					
32	43.2	135	18	100	4	19	70.71					
40	49.1	140	18	105	4	19	74.25					
50	61.1	155	18	120	8	19	45.92					
65	77.1	175	20	140	8	19	53.58					
80	90.0	200	22	160	8	23	61.23					
100	115.4	225	24	185	8	23	70.80					
125	141.2	270	26	225	8	25	86.10					
150	166.6	305	28	260	12	25	67.29					
200	218.0	350	30	305	12	25	78.94					
250	269.5	430	34	380	12	27	98.35					
300	321.0	480	36	430	16	27	83.89					

承認 滝川	材質 SUSF304	名称 呼び圧力20Kフランジ 差込み溶接フランジ FF	図面番号 19514
検図 西久保	尺度 フリー		
製図 芦田	日付 2019/11/15	inoc イノック株式会社	