



呼び径 (A)	フランジ各部の寸法										寸法許容差					
	差込み 穴の径 d	外径 D	厚さ t	中心円		ボルト穴		隣接穴 のピッチ P	ガスケット座		d	D	t-f	C	P	g
				の径 C	数 n	径 h	径 g		径 f							
10	17.8	90	14	65	4	15	45.96	46	1	+1.0 0	±1.5	+1.5 0	±0.8	±0.8	±0.8	
15	22.2	95	14	70	4	15	49.50	51	1							
20	27.7	100	16	75	4	15	53.03	56	1							
25	34.5	125	16	90	4	19	63.64	67	1							
32	43.2	135	18	100	4	19	70.71	76	2							
40	49.1	140	18	105	4	19	74.25	81	2							
50	61.1	155	18	120	8	19	85.92	96	2							
65	77.1	175	20	140	8	19	93.58	116	2							
80	90.0	200	22	160	8	23	101.23	132	2							
100	115.4	225	24	185	8	23	110.80	160	2							
125	141.2	270	26	225	8	25	121.10	195	2							
150	166.6	305	28	260	12	25	132.29	230	2							
200	218.0	350	30	305	12	25	158.94	275	2							
250	269.5	430	34	380	12	27	190.35	345	2							
300	321.0	480	36	430	16	27	222.89	395	3							

承認 滝川	材質 SUSF304	名称 呼び圧力20Kフランジ	図面番号 19516
検図 西久保	尺度 フリー	平面座差込み溶接フランジ RF	
製図 芦田	日付 2019/11/15	inoç イノック株式会社	