



| 呼び径 (A) | フランジ各部の寸法 | | | | | | | | 寸法許容差 | | | | |
|------------|-----------|---------|------------|--------|--------|--------------|--------|---|-------|-----------|------|------|------|
| | 外径 D | 厚さ t | 中心円の径 C | ボルト穴 | | 隣接穴のピッチ P | ガスケット座 | | D | t-f | C | P | g |
| | | | | 数 n | 径 h | | g | f | | | | | |
| 10 | 90 | 14 | 65 | 4 | 15 | 45.96 | 46 | 1 | ±1.5 | +1.5 0 | ±0.8 | ±0.8 | ±0.8 |
| 15 | 95 | 14 | 70 | 4 | 15 | 49.50 | 51 | 1 | | | | | |
| 20 | 100 | 16 | 75 | 4 | 15 | 53.03 | 56 | 1 | | | | | |
| 25 | 125 | 16 | 90 | 4 | 19 | 63.64 | 67 | 1 | | | | | |
| 32 | 135 | 18 | 100 | 4 | 19 | 70.71 | 76 | 2 | | | | | |
| 40 | 140 | 18 | 105 | 4 | 19 | 74.25 | 81 | 2 | | | | | |
| 50 | 155 | 18 | 120 | 8 | 19 | 45.92 | 96 | 2 | | | | | |
| 65 | 175 | 20 | 140 | 8 | 19 | 53.58 | 116 | 2 | | | | | |
| 80 | 200 | 22 | 160 | 8 | 23 | 61.23 | 132 | 2 | | | | | |
| 100 | 225 | 24 | 185 | 8 | 23 | 70.80 | 160 | 2 | | | | | |
| 125 | 270 | 26 | 225 | 8 | 25 | 86.10 | 195 | 2 | | | | | |
| 150 | 305 | 28 | 260 | 12 | 25 | 67.29 | 230 | 2 | | | | | |
| 200 | 350 | 30 | 305 | 12 | 25 | 78.93 | 275 | 2 | | | | | |
| 250 | 430 | 34 | 380 | 12 | 27 | 98.35 | 345 | 2 | | | | | |
| 300 | 480 | 36 | 430 | 16 | 27 | 83.89 | 395 | 3 | | | | | |

| | | | |
|----------|------------------|-------------------------------------|---------------|
| 承認 滝川 | 材質 SUSF 304 | 名称 呼び圧力20Kフランジ 平面座閉止フランジ BDRF | 図面番号 19520 |
| 検図 今西 | 尺度 フリー | inoć イノック株式会社 | |
| 製図 芦田 | 日付 2019/11/19 | | |