


呼び径		各部の寸法					二面幅 S		材質
A (mm)	B (inch)	R	Rc	L	E	f	八角	十角	
25×8	1× ¹ / ₄	R 1	Rc ¹ / ₄	27	20	9	35		②
25×15	1× ¹ / ₂	R 1	Rc ¹ / ₂	27	20	13	35		①
25×20	1× ³ / ₄	R 1	Rc ³ / ₄	27	20	15	35		①
32×15	1 ¹ / ₄ × ¹ / ₂	R 1 ¹ / ₄	Rc ¹ / ₂	32.5	23.5	12	43		②
32×20	1 ¹ / ₄ × ³ / ₄	R 1 ¹ / ₄	Rc ³ / ₄	32.5	23.5	13	43		②
32×25	1 ¹ / ₄ ×1	R 1 ¹ / ₄	Rc 1	32.5	23.5	15	43		②
40×15	1 ¹ / ₂ × ¹ / ₂	R 1 ¹ / ₂	Rc ¹ / ₂	33.5	23.5	15	49		②
40×20	1 ¹ / ₂ × ³ / ₄	R 1 ¹ / ₂	Rc ³ / ₄	33.5	23.5	13	49		②
40×25	1 ¹ / ₂ ×1	R 1 ¹ / ₂	Rc 1	33.5	23.5	15	49		②
40×32	1 ¹ / ₂ ×1 ¹ / ₄	R 1 ¹ / ₂	Rc 1 ¹ / ₄	33.5	23.5	21	49		②
50×20	2× ³ / ₄	R 2	Rc ³ / ₄	37.5	26.5	13	61		②
50×25	2×1	R 2	Rc 1	37.5	26.5	15	61		②
50×32	2×1 ¹ / ₄	R 2	Rc 1 ¹ / ₄	37.5	26.5	17	61		②
50×40	2×1 ¹ / ₂	R 2	Rc 1 ¹ / ₂	37.5	26.5	17	61		②
65×40	2 ¹ / ₂ ×1 ¹ / ₂	R 2 ¹ / ₂	Rc 1 ¹ / ₂	39	28	18		80	②
65×50	2 ¹ / ₂ ×2	R 2 ¹ / ₂	Rc 2	39	28	20		80	②
80×40	3×1 ¹ / ₂	R 3	Rc 1 ¹ / ₂	44	32	18		95	②
80×50	3×2	R 3	Rc 2	44	32	20		95	②
80×65	3×2 ¹ / ₂	R 3	Rc 2 ¹ / ₂	44	32	23		95	②

(注記) 管用ねじ部はJIS B 0203:1999による。

*材質①SUS F304, ②SCS 13A。

承認 芦田	材質 SUS F304 SCS 13A	製品名 ブッシング	図面番号 20183
検図 今西	尺度 フリー	製品コード B	
製図 滝川	日付 2021.6.10	 イノック株式会社	