


呼び径 (A)	フランジ各部の寸法									寸法許容差					
	差込み 穴の径 d	外径 D	厚さ t	中心円		隣接穴 のピッチ P	ガスケット座		d	D	t-f	C	P	g	
				径 C	数 n		径 h	g							f
10	17.8	90	14	65	4	15	45.96	46	1	+1.0 0	±1.5	+1.5 0	±0.8	±0.8	±0.8
15	22.2	95	14	70	4	15	49.50	51	1						
20	27.7	100	16	75	4	15	53.03	56	1						
25	34.5	125	16	90	4	19	63.64	67	1						
32	43.2	135	18	100	4	19	70.71	76	2						
40	49.1	140	18	105	4	19	74.25	81	2						
50	61.1	155	18	120	8	19	45.92	96	2						
65	77.1	175	20	140	8	19	53.58	116	2						
80	90.0	200	22	160	8	23	61.23	132	2						
100	115.4	225	24	185	8	23	70.80	160	2						
125	141.2	270	26	225	8	25	86.10	195	2						
150	166.6	305	28	260	12	25	67.29	230	2						
200	218.0	350	30	305	12	25	78.94	275	2						
250	269.5	430	34	380	12	27	98.35	345	2						
300	321.0	480	36	430	16	27	83.89	395	3						

承認 滝川	材質 SUSF304	名称 呼び圧力20Kフランジ	図面番号 23098
検図 今西	尺度 フリー	平面座差込み溶接フランジ RF	
製図 滝川	日付 2023/03/13	 イノック株式会社	