



呼び径 (A)	フランジ各部の寸法								寸法許容差				
	外径 D	厚さ t	中心円 の径 C	ボルト穴		隣接穴 のピッチ P	ガスケット座		D	t-f	C	P	g
				数 n	径 h		g	f					
10	90	14	65	4	15	45.96	46	1	±1.5	+1.5 0	±0.8	±0.8	±0.8
15	95	14	70	4	15	49.50	51	1					
20	100	16	75	4	15	53.03	56	1					
25	125	16	90	4	19	63.64	67	1					
32	135	18	100	4	19	70.71	76	2					
40	140	18	105	4	19	74.25	81	2					
50	155	18	120	8	19	45.92	96	2					
65	175	20	140	8	19	53.58	116	2					
80	200	22	160	8	23	61.23	132	2					
100	225	24	185	8	23	70.80	160	2					
125	270	26	225	8	25	86.10	195	2					
150	305	28	260	12	25	67.29	230	2					
200	350	30	305	12	25	78.93	275	2					
250	430	34	380	12	27	98.35	345	2					
300	480	36	430	16	27	83.89	395	3					

承認 滝川	材質 SUSF304	名称 呼び圧力20Kフランジ 平面座閉止フランジ BDRF	図面番号 23102
検図 今西	尺度 フリー		
製図 滝川	日付 2023/03/13	<b>inoć</b> イノック株式会社	