



呼び径①×②		OD1	OD2	S20S				H	許容差						
A	B			ID1	T1	ID2	T2		OD1	OD2	ID1	ID2	T1・2	H	
100×80	4×3	114.3	89.1	106.3	4.0	81.1	4.0	101.6	±1.6	±1.6	±1.6	±1.6	+規定 -12.5%	±1.6	
100×65	4×2½	114.3	76.3	106.3	4.0	69.3	3.5	101.6		+1.6					±0.8
100×50	4×2	114.3	60.5	106.3	4.0	53.5	3.5	101.6		-0.8					±0.8
125×100	5×4	139.8	114.3	129.8	5.0	106.3	4.0	127.0	+2.4 -1.6	±1.6	±1.6	±1.6	+規定 -12.5%	±1.6	
125×80	5×3	139.8	89.1	129.8	5.0	81.1	4.0	127.0		±1.6					±1.6
125×65	5×2½	139.8	76.3	129.8	5.0	69.3	3.5	127.0		+1.6 -0.8					±0.8
150×125	6×5	165.2	139.8	155.2	5.0	129.8	5.0	139.7	+2.4 -1.6	+2.4 -1.6	±1.6	+規定 -12.5%	±1.6		
150×100	6×4	165.2	114.3	155.2	5.0	106.3	4.0	139.7		±1.6				±1.6	
150×80	6×3	165.2	89.1	155.2	5.0	81.1	4.0	139.7		±1.6				±1.6	
200×150	8×6	216.3	165.2	203.3	6.5	155.2	5.0	152.4	+4.0 -3.2	+2.4 -1.6	±1.6	+規定 -12.5%	±2.4		
200×125	8×5	216.3	139.8	203.3	6.5	129.8	5.0	152.4		±1.6				±1.6	
200×100	8×4	216.3	114.3	203.3	6.5	106.3	4.0	152.4		±1.6				±1.6	
250×200	10×8	267.4	216.3	254.4	6.5	203.3	6.5	177.8	+4.0 -3.2	+2.4 -1.6	±3.2	+規定 -12.5%	±2.4		
250×150	10×6	267.4	165.2	254.4	6.5	155.2	5.0	177.8		±3.2				±3.2	
250×125	10×5	267.4	139.8	254.4	6.5	129.8	5.0	177.8		±3.2				±3.2	
300×250	12×10	318.5	267.4	305.5	6.5	254.4	6.5	203.2	+4.0 -3.2	+4.0 -3.2	±3.2	+規定 -12.5%	±2.4		
300×200	12×8	318.5	216.3	305.5	6.5	203.3	6.5	203.2		±1.6				±1.6	
300×150	12×6	318.5	165.2	305.5	6.5	155.2	5.0	203.2		±1.6				±1.6	

※ ベベルエンドの形状、寸法は J I S B 2313「配管用鋼板製突合せ溶接式管継手」による
 ※ 管継手の直角度の許容値は J I S B 2313「配管用鋼板製突合せ溶接式管継手」による

承認 滝川	材質 SUS 316W	名称 同心レジューサー RC(S20S)	図面番号 17255
検図 芦田	尺度 フリー		
製図 滝川	日付 2017/7/28	 イノック株式会社	