



| 呼び径①×②×③ | | OD1 | OD2 | S40 | | | | C | M | 許容差 | | | | | |
|-------------|----------|-------|-------|-------|------|-------|-----|-------|-------|--------------|--------------|------|----------------------|------|-----|
| A | B | | | ID1 | T1 | ID2 | T2 | | | OD1 | OD2 | ID1 | ID2 | T1・2 | C・M |
| 100×100×80 | 4×4×3 | 114.3 | 89.1 | 102.3 | 6.0 | 78.1 | 5.5 | 104.8 | 98.4 | ±1.6 | ±1.6 | ±1.6 | ±0.8 | ±1.6 | |
| 100×100×65 | 4×4×2½ | 114.3 | 76.3 | 102.3 | 6.0 | 65.9 | 5.2 | 104.8 | 95.3 | | +1.6 -0.8 | | | | |
| 100×100×50 | 4×4×2 | 114.3 | 60.5 | 102.3 | 6.0 | 52.7 | 3.9 | 104.8 | 88.9 | | ±1.6 | | | | |
| 125×125×100 | 5×5×4 | 139.8 | 114.3 | 126.6 | 6.6 | 102.3 | 6.0 | 123.8 | 117.5 | ±1.6 | ±1.6 | ±1.6 | ±1.6 | | |
| 125×125×80 | 5×5×3 | 139.8 | 89.1 | 126.6 | 6.6 | 78.1 | 5.5 | 123.8 | 111.1 | | +1.6 -0.8 | | | | |
| 125×125×65 | 5×5×2½ | 139.8 | 76.3 | 126.6 | 6.6 | 65.9 | 5.2 | 123.8 | 108.0 | | +2.4 -1.6 | | | | |
| 150×150×125 | 6×6×5 | 165.2 | 139.8 | 151.0 | 7.1 | 126.6 | 6.6 | 142.9 | 136.5 | +2.4 -1.6 | ±1.6 | ±1.6 | +規定 しない -12.5% | | |
| 150×150×100 | 6×6×4 | 165.2 | 114.3 | 151.0 | 7.1 | 102.3 | 6.0 | 142.9 | 130.2 | | ±1.6 | | | | |
| 150×150×80 | 6×6×3 | 165.2 | 89.1 | 151.0 | 7.1 | 78.1 | 5.5 | 142.9 | 123.8 | | ±1.6 | | | | |
| 200×200×150 | 8×8×6 | 216.3 | 165.2 | 199.9 | 8.2 | 151.0 | 7.1 | 177.8 | 168.3 | +2.4 -1.6 | ±1.6 | ±1.6 | ±1.6 | | |
| 200×200×125 | 8×8×5 | 216.3 | 139.8 | 199.9 | 8.2 | 126.6 | 6.6 | 177.8 | 161.9 | | ±1.6 | | | | |
| 200×200×100 | 8×8×4 | 216.3 | 114.3 | 199.9 | 8.2 | 102.3 | 6.0 | 177.8 | 155.6 | | ±1.6 | | | | |
| 250×250×200 | 10×10×8 | 267.4 | 216.3 | 248.8 | 9.3 | 199.9 | 8.2 | 215.9 | 203.2 | +4.0 -3.2 | ±3.2 | ±3.2 | ±2.4 | | |
| 250×250×150 | 10×10×6 | 267.4 | 165.2 | 248.8 | 9.3 | 151.0 | 7.1 | 215.9 | 193.7 | | +2.4 -1.6 | | | | |
| 250×250×125 | 10×10×5 | 267.4 | 139.8 | 248.8 | 9.3 | 126.6 | 6.6 | 215.9 | 190.5 | | ±1.6 | | | | |
| 300×300×250 | 12×12×10 | 318.5 | 267.4 | 297.9 | 10.3 | 248.8 | 9.3 | 254.0 | 241.3 | +2.4 -1.6 | ±1.6 | ±1.6 | ±1.6 | | |
| 300×300×200 | 12×12×8 | 318.5 | 216.3 | 297.9 | 10.3 | 199.9 | 8.2 | 254.0 | 228.6 | | +4.0 -3.2 | | | | |
| 300×300×150 | 12×12×6 | 318.5 | 165.2 | 297.9 | 10.3 | 151.0 | 7.1 | 254.0 | 219.1 | | ±1.6 | | | | |

※ ベベルエンドの形状、寸法はJIS B 2313「配管用鋼板製突合せ溶接式管継手」による

※ 管継手の直角度の許容値はJIS B 2313「配管用鋼板製突合せ溶接式管継手」による

| | | | |
|----------|-----------------|---------------|---------------|
| 承認 滝川 | 材質 SUS 316W | 名称 径違いチーズ | 図面番号 17265 |
| 検図 芦田 | 尺度 フリー | TR(S40) | |
| 製図 滝川 | 日付 2017/8/03 | inoç イノック株式会社 | |