



呼び径①×②×③		S40								許容差					
A	B	OD1	OD2	ID1	T1	ID2	T2	C	M	OD1	OD2	ID1	ID2	T1・2	C・M
20X20X15	3/4X3/4X1/2	27.2	21.7	21.4	2.9	16.1	2.8	28.6	28.6						
25X25X20	1X1X3/4	34.0	27.2	27.2	3.4	21.4	2.9	38.1	38.1						
25X25X15	1X1X1/2	34.0	21.7	27.2	3.4	16.1	2.8	38.1	38.1						
32X32X25	1 1/4X1 1/4X1	42.7	34.0	35.5	3.6	27.2	3.4	47.6	47.6						
32X32X20	1 1/4X1 1/4X3/4	42.7	27.2	35.5	3.6	21.4	2.9	47.6	47.6						
32X32X15	1 1/4X1 1/4X1/2	42.7	21.7	35.5	3.6	16.1	2.8	47.6	47.6						
40X40X32	1 1/2X1 1/2X1 1/4	48.6	42.7	41.2	3.7	35.5	3.6	57.2	57.2	+1.6					
40X40X25	1 1/2X1 1/2X1	48.6	34.0	41.2	3.7	27.2	3.4	57.2	57.2	-0.8					
40X40X20	1 1/2X1 1/2X3/4	48.6	27.2	41.2	3.7	21.4	2.9	57.2	57.2		+1.6			±0.8	規定 しない
50X50X40	2X2X1 1/2	60.5	48.6	52.7	3.9	41.2	3.7	63.5	60.3		-0.8				±1.6
50X50X32	2X2X1 1/4	60.5	42.7	52.7	3.9	35.5	3.6	63.5	57.2						-12.5%
50X50X25	2X2X1	60.5	34.0	52.7	3.9	27.2	3.4	63.5	50.8						
65X65X50	2 1/2X2 1/2X2	76.3	60.5	65.9	5.2	52.7	3.9	76.2	69.9						
65X65X40	2 1/2X2 1/2X1 1/2	76.3	48.6	65.9	5.2	41.2	3.7	76.2	66.7						
80X80X65	3X3X2 1/2	89.1	76.3	78.1	5.5	65.9	5.2	85.7	82.6						
80X80X50	3X3X2	89.1	60.5	78.1	5.5	52.7	3.9	85.7	76.2	±1.6					
80X80X40	3X3X1 1/2	89.1	48.6	78.1	5.5	41.2	3.7	85.7	73.0						

※ ベベルエンドの形状、寸法はJIS B 2313「配管用鋼板製突合せ溶接式管継手」による

※ 管継手の直角度の許容値はJIS B 2313「配管用鋼板製突合せ溶接式管継手」による

承認 滝川	材質 SUS 316LW	名称 径違いチーズ	図面番号
検図 芦田	尺度 フリー	TR(S40)	17289
製図 滝川	日付 2017/8/08	inoç イノック株式会社	